

SHURE BETA 58 A - dinamički vokalni mikrofon

Šifra: 6234

Kategorija proizvoda: Dinamički

Proizvođač: Shure

Cena: 185,00 EUR



Pravo odbijanja i povrata za ovaj proizvod ne vrijedi, budući da proizvod spada u pravne iznimke prema čl. 16 Direktive 2011/83/EU Europskog parlamenta i Vijeća od 25. 10. 2011. - isporuka zapečaćene robe koja je otpečaćena nakon isporuke i ne može se vratiti zbog razloga vezanih za higijenu ili zaštitu zdravlja.

The Shure Beta 58A® is a high-output supercardioid dynamic vocal microphone designed for professional sound reinforcement and project studio recording. It has become a leading choice among vocalists and touring professionals worldwide.

The Beta 58A maintains a true supercardioid pattern throughout its frequency range. This insures high gain before feedback, maximum isolation from other sound sources, and minimum off-axis tone coloration. The Beta 58A has a shaped frequency response that is ideal for close-up vocals. The superb performance of this microphone is not affected by rough handling because of its rugged construction, proven shock mount system, and hardened steel mesh grille.

Frequency response tailored for vocals, with brightened midrange and bass rolloff to control proximity effect

Uniform supercardioid pattern for high gain before feedback and superior rejection of off-axis sound

Neodymium magnet for high signal-to-noise output

Hardened steel mesh grille that resists wear and abuse

Advanced pneumatic shock mount system that minimizes transmission of mechanical noise and vibration

Minimally effected by varying load impedance

Legendary Shure quality and reliability

TypeDynamic (moving coil) **Frequency Response**50 to 16,000 Hz

NOTE: The curve above shows on-axis response at a distance of 2 feet from a uniform sound source. Your response may vary, depending on microphone position. **Polar Pattern**Supercardioid, rotationally symmetrical about microphone axis, uniform with frequency. **Output Level** (at 1,000 Hz)Open Circuit Voltage: -51.5 dBV/Pa* (2.6 mV)*1 Pa = 94 dB SPL **Impedance**Rated impedance is 150 ohms (290 ohms actual) for connection to microphone inputs rated low Z Phasing.Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3. **Case**Silver blue enamel-painted die cast metal with hardened, matte-finished, spherical steel mesh grille. **Adjustable, Stand Adapter**Slip-in microphone mounting, unbreakable, adjustable through 180 degrees with standard 5/8"-27 thread, black finish.

DimensionsSee User Guide. **Net Weight**278 grams (9.92 oz)