

MARTIN T Rex

Šifra: 6297

Kategorija proizvoda: Klub i stage

Proizvođač: Martin Profesional

Cena: 229,00 EUR

Raptor. Together they form a deadly new partnership.

Fast and furious, the T-Rex deploys its unique quad angled mirror to create a devastating salvo of effects: light beams with razor sharp intensity slice through the air, changing color and direction to the beat of the music.

And being a cold-blooded monster, the T-Rex remains cool at all times. Its high-speed cooling fan means the T-Rex is ready for action all night long.

250 W halogen lamp

Combined color and gobo wheel

19 gobos plus open

Safety approvals CE

Music triggered

1000 hour lamp included

12 gobos

Faceted rotating parabolic reflector

Rigorously tested for total reliability

Continuous operation - no cool down time needed

Physical

Length: 490 mm (19.3 in.)

Height: 190 mm (7.5 in.)

Width: 164 mm (6.5 in.)

Weight: 7.5 kg (16.5 lbs.)

Lamp

Type: 250 W, 24 V ELC halogen

Socket: GX 5.3

Fitted as standard: Philips ELC 10H 250 W (1000 hrs.)

Approved alternative lamp(s): Osram ELC 24 V/250 W (50 hrs.), Osram ELC-7/X 24 V/250 W (700 hrs.)

Dynamic Effects

Color/gobo wheel: 19 pattern gobos (11 single color, 4 multi-color, 4 non-color) + open

Motorized rotating parabolic mirror dish: Multi-facet, continuous rotation

Motorized mirror: Quadruple angle, continuous rotation

Optics

Manual focus: 2 m (6.6 ft.) - 20 m (65.6 ft.)

Control and Programming

Control: Music trig, automatic level sensitivity adjustment

Construction

Housing: Steel and aluminum

Installation

Mounting points: Adjustable floorstand/mounting bracket

Orientation: Any

MARTIN T Rex

**The
T-**

Rex is a 250 W scanner featuring a quad angled mirror for aggressive mid-air effects and a combined color/gobo wheel offering multiple colors and a full array of 19 gobo patterns.

An awesome force has evolved...and it's the most dangerous threat yet to lower light forms. King of its habitat, the T-Rex is the aggressive new companion to Martin's other famous predator, the

Connections

AC power input: 3-pin IEC male socket

Electrical

AC power: 110-120 V, 50/60 Hz (US model)

AC power: 230-240 V, 50/60 Hz (EU model)

Main fuse: US model 5.0 AT, EU model 2.5 AT (both slow blow)

Thermal

Cooling: Forced air


Maximum ambient temperature (Ta max.): 40° C (104° F)

Maximum surface temperature, steady state, Ta=40° C: 60° C (140° F)

Total heat dissipation (calculated, +/- 10%): 920 BTU/hr.

Downloads

Image not found or type unknown



[Product Guide vol 10](#)

Image not found or type unknown



[T-Rex Screensaver](#)

Approvals

Image not found or type unknown



EU safety: EN 60598-2-17

EU EMC: EN 55 015, EN 55 103-1, EN 61 547