

RELOOP sPodcaster Go

Šifra: 15029
Kategorija proizvoda: Usb i Broadcast
Proizvođač: Reloop

Cena: **80,00** EUR

Pravo odbijanja i povrata za ovaj proizvod ne vrijedi, budući da proizvod spada u pravne iznimke prema čl. 16 Direktive 2011/83/EU Europskog parlamenta i Vijeća od 25. 10. 2011. - isporuka zapečaćene robe koja je otpečaćena nakon isporuke i ne može se vratiti zbog razloga vezanih za higijenu ili zaštitu zdravlja.

The cardioid polar pattern keeps the sound of your room at a minimum, focusing audio capture on what's in front of the capsule. Plug your headphones directly into the mic to monitor your audio as you record with low latency, and use the volume buttons to control the headphone level. A prominent mic-mute button is on hand for muting the signal at will.

The mic records at 16-bit/48 kHz. It includes a storage bag, a desktop stand, and a micro USB cable for plugging the mic into your computer.

USB condenser microphone for portable podcasting
Suitable for vocal and instrumental recordings
Suitable for recording on the go and smaller studio environments
Cardioid polar pattern
Bus-powered over USB 2.0 connection
Plug-and-play for Mac and Windows
Integrated class-compliant USB audio interface
Connect directly to mic to monitor recordings from computer
Low-latency transmission
Volume +/- buttons for adjusting headphone output
Large mic-mute button on the front
16-bit / 48 kHz
Micro-USB and 3.5mm jack
Rigid design made of lightweight aluminum
Smart foldable stand construction, removable and with M10 thread as well as transport pouch

Microphone
Primary Applications Podcast, Web-Streaming, Conferencing
Form Factor Desktop / Stand/Boom Mount
Intended Sound Sources Vocals, Speech/Voice Over, Instrument
Sound Field Mono

Capsule Condenser
Polar Pattern Cardioid
Orientation Side Address
Circuitry Solid-State
High-Pass Filter None
Gain Adjustment Yes
On-Board Controls Headphone Volume, Mic Mute
Performance
Frequency Range 50 Hz to 18 kHz
Maximum SPL 115 dB SPL
Sensitivity 44 dB at 1 kHz
Dynamic Range 93 dB
Signal-to-Noise Ratio 59 dB
Connectivity
Output Connectors (Analog) None
Output Connectors (Digital) 1 x Micro-USB
Headphone Connector 1 x 1/8" / 3.5 mm
Digital Audio
A/D Conversion 16-Bit
Sample Rate 48 kHz
Operating System Support Windows, macOS/OS X
Power
Bus Power USB
Operating Voltage 5 V
Operating Current Consumption 500 mA
Physical
Color Black
Mounting Desktop Stand (Included)
Mounting Thread Size 3/8"-16 Female
Construction Material Aluminum
Dimensions H: 5.8 x W: 2.5 x L: 1.7" / H: 146.2 x W: 63 x L: 42.8 mm
Weight 4.9 oz / 140 g
Packaging Info
Package Weight 0.815 lb
Box Dimensions (LxWxH) 8.35 x 6.4 x 3.45"