

MACKIE ProFx6 V3 - mikseta bez snage

Šifra: 15479

Kategorija proizvoda: Miksete bez snage

Proizvođač: MACKIE

Cena: 175,00 EUR

TRS headphone output includes an independent level control. Other features include Input-USB 1-2 blend control, FX mute, and FX to main.

Features

Professional Sound Quality

Equipped with 2 Onyx Mic Pres offering up to 60 dB of gain and ultralow noise performance

All-new GigFX Effects Engine with 24 different FX options, from reverbs to delays and more

Essential Mixing Tools

2-band EQ (80 Hz and 12 kHz) on channels 1/2

Hi-Z switches allows direct connection of guitars, basses, and other instruments

100 Hz low-cut filter and 48V phantom power on all mic channels

Line inputs on channel 3/4

Stereo 1/8" input on channel 5/6

Headphone output with separate level and blend control

24-Bit / 192 kHz 2x4 USB Recording Interface

2x4 USB I/O allows you to create two custom mixes on your computer to send back in to the mixer

Perfect for live performance recording, music playback, live streaming, and more

Latency-Free Monitoring

Easily blend between monitoring your computer's output and a direct feed from the mixer

Professional Production Content

Pro Tools | First and Waveform OEM professional software and plugin packages included

The Musician Collection for ProTools | First includes 23 plugins including 304 EQ, 304C Compressor, BBD Delay, Black Op Distortion, Black Shiny Wah, Black Spring Reverb, C1 Chorus, DC Distortion, Eleven Lite, Flanger, Graphic EQ, Gray Compressor, Green JRC Overdrive, In-Tune, Orange Phaser, Roto Speaker, Sci-Fi, Studio Reverb, Tape Echo, Tri Knob Fuzz, Vari-Fi, Vibe, Phaser, and White Boost

The DAW Essentials Bundle for Waveform OEM includes 16 powerful plugins like Equalizer, Compressor, Reverber8, and Limiter

Signature Rugged Design

Mackie built-like-a-tank design

Solid steel chassis protects your investment

Tough ABS side protection

Mixer

Number of Analog Input Channels 6

Number of Mic Preamps 2

Analog Output Channels 2 x Stereo Master Output

1 x Stereo Headphone Output

Meters Main Meter:

2 x 8-Segment LED

Meter Range Main Meter:

MACKIE ProFx6 V3 - mikseta bez snage

Channels 1-2 offer combo XLR-1/4" mic/line connections and feature Hi-Z (for guitar and bass), low-cut filters (100 Hz), gain controls, 2-band EQ, stereo linking, level faders, and FX send. Channels 3-4 offer two 1/4" inputs and feature a level control, while channels 5-6 use a 3.5mm stereo input with level fader. Engaging channel 5-6's USB3-4 switch will override the 3.5" input and enables the USB return from a computer. The master output is controlled with a dedicated level knob and features XLR and 1/4" connectors, while the dedicated 1/4"

-24 dB to +14 dB Plus Peak/Clip

Signal Processing

EQ Parameters Low: ± 15 dB at 80 Hz

High: ± 15 dB at 12 kHz

Filters High-Pass: 100 Hz, 18 dB/Octave

Built-In Effects 24 x Preset (Factory)

Digital Audio

Bit Depth 24-Bit

Performance

Frequency Response Mic Input to Output:

20 Hz to 30 kHz $+0/-1$ dB (Unity Gain)

Max Input Level +22 dB

Output Level Main Output:

+28 dBu at Max Gain

All Other Output:

+22 dBu at Max Gain

I/O Impedance Mic Input:

3.8 Kilohms

Insert Return:

10 Kilohms

Line Input:

≥ 20 Kilohms

Headphone Output:

25 Ohms

Main Output:

120 Ohms (Unbalanced)

240 Ohms (Balanced)

Crosstalk Adjacent Inputs:

-90 dB at 1 kHz

Input to Output:

-80 dB at 1 kHz

Fader Off:

-75 dB at 1 kHz

Muted:

-90 dB at 1 kHz

CMRR 70 dB at Max Gain (1 kHz, Mic In to Main Out)

EIN -126 dBu at Max Gain (150-Ohm Input)

Noise Floor All Outputs:

-95 dBu (Master Level at $-\infty$, Channel Levels at $-\infty$)

-80 dBu (Master Level at Unity, One Channel Level at Unity)

THD+N Mic Input to Main Output:

$< 0.03\%$ (+4 dBu)

Connectivity

Phantom Power +48 V, Selectable On/Off (Applied to All Inputs)

USB 1 x USB Type-B (USB 2.0)

USB I/O Capacity 2 x Input / 4 x Output

Power

AC Input Power Universal:

100 to 240 VAC, 50 / 60 Hz

Power Supply Output 12 VDC at 2 A

Physical

Rack Mountable No

Dimensions 2.9 x 7.5 x 8.4" / 7.1 x 19 x 21.3 cm

Weight 2.6 lb / 1.2 kg

Packaging Info

Package Weight 4 lb

Box Dimensions (LxWxH) 19 x 13 x 9"