

FOCAL ALPHA 65

Image not found or type unknown

FOCAL ALPHA 65

Šifra: 9854

Kategorija proizvoda: Studijski monitori

Proizvođač: Focal

Cena: 359,55 EUR

Between its frequency response of 40 Hz to 22 kHz, the monitor is neutral and accurate. You can drive it with unbalanced or balanced audio and adjust the sensitivity to match. Mount it against the wall, or on the wall itself for multichannel immersive audio formats. An IEC power cable is included, as is a protective grille for the woofer.

Excellent Dynamics, Balanced Sound

Stocked with Focal's exclusive, French-manufactured Slatefiber woofer, the Focal 65 EVO provides an excellent presentation of dynamic range. You'll also notice that the speaker is quite balanced: you'll get the same sonic picture throughout your monitoring environment, not just in the sweetspot; and, the monitors have been engineered to give you the same frequency balance at any loudness.

Flexible Mounting

This monitor is built to be used in a variety of ways. Mount it on a stand, in a traditional nearfield setup, or use the built-in insert to mount the speaker to a wall for immersive formats, such as Dolby Atmos.

A Variety of Inputs

Dedicated XLR, 1/4" TRS, and RCA inputs are on hand, so you're covered for pretty much any professional or high-end consumer analog connection.

Comprehensive Room EQ

Adjust the low-midrange or the high end to better suit your environment. You'll note a filter adjustable between 0 and 300 Hz (± 6 dB), as well as a treble-centric one selectable between 4.5 and 22 kHz (± 3 dB).

Focal Alpha-65 Evo Specs

Studio Monitor

Monitor Type Active 2-Way

Enclosure Bass-Reflex

Power Rating 80 W

Drivers HF Driver: 1 x 1" / 2.5 cm Aluminum Dome

Low-Mid Driver: 1 x 6.5" / 16.5 cm Cone

Amplification 1 x LF Amplifier: Class-D Rated at 55 W

1 x HF Amplifier: Class-D Rated at 25 W

Performance

Frequency Range 40 Hz to 22 kHz

Maximum Sound Pressure Level (SPL) 104 dB

Analog Input Sensitivity/Gain +6 dB / 0 dB (Fixed)

Phase Adjustment None

Signal Processing

EQ 1 x HF Shelf: -3 to +3 dB at 4.5 kHz

1 x LF Shelf: -6 to +6 dB at 300 Hz

Filters None

Parametric EQ None

Connectivity

Audio I/O 1 x 1/4" TRS Balanced Female Analog Input (10 Kilohms)

1 x XLR Balanced Female Analog Input (10 Kilohms)

1 x RCA Unbalanced Female Analog Input (10 Kilohms)

Power

AC Input Power 100 to 240 VAC, 50/60 Hz

Power Consumption 0.5 W (Standby)

General

Enclosure Material MDF

Dimensions (W x H x D) 11.4 x 10.3 x 13.4" / 29 x 26.2 x 34 cm

Weight 16.8 lb / 7.6 kg

Packaging Info

Package Weight 21 lb

Box Dimensions (LxWxH) 18 x 15.3 x 14"