

FOCAL SOLO6 ST6 RED (komad) - aktivni studijski monitor

Šifra: 16360
Kategorija proizvoda: Studijski monitori
Proizvođač: Focal

Cena: 1.389,00 EUR

video monitors and other electronic equipment.

Beryllium inverted dome tweeter: very low directionality, excellent linearity, and dynamics
Optimized baffle tweeter: excellent dispersion control
Composite sandwich W-cone: sound neutrality, no distortion
Focus mode: two monitors in one; 2-way monitor and 1-way full-range monitor (woofer alone)
Large laminar port: no port noises or distortion
Inserts for wall fastening
Automatic stand-by mode for power saving
Settings: LF shelving, HF shelving, LPF at 160 Hz

Focal FOPRO-SOLO6ST6 Specs
Studio Monitor
Monitor Type Active 2-Way
Enclosure Bass-Reflex, Shielded
Power Rating 130 W RMS
Drivers HF Driver: 1 x 1.5" / 3.8 cm Beryllium Inverted Dome Tweeter
LF Driver: 1 x 6.5" / 16.5 cm Composite Woofer
Amplification 1 x HF Amplifier: Rated at 50 W RMS
1 x LF Amplifier: Rated at 80 W RMS
Performance
Frequency Response 45 Hz to 40 kHz $\pm$ 3 dB
Maximum Sound Pressure Level (SPL) 110 dB
Signal Processing
EQ 1 x HF Shelf: -3 to +3 dB at 5 kHz (Continuously Variable dB Increments)
1 x LF Shelf: -3 to +3 dB at 150 Hz (Continuously Variable dB Increments)
1 x Mid Notch/Peak: -3 to +3 dB at 160 Hz
Filters 1 x High-Pass at 45 to 90 Hz
Parametric EQ None
Connectivity
Audio I/O 1 x XLR Balanced Female Analog Input (10 Kilohms)
Power
AC Input Power 100 to 240 VAC, 50/60 Hz
General
Enclosure Material MDF
Dimensions (W x H x D) 9.7 x 13.1 x 11.6" / 24.6 x 33.4 x 29.5 cm

FOCAL SOLO6 ST6 RED (komad) - aktivni studijski monitor
is powered by its own amplifier for a total of 130W of RMS power for a strong, distortion-free performance. The rear panel offers a standard XLR input connector, which allows you to connect virtually any professional sound system. It also has a high-pass filter, shelving EQs for low and high frequencies, and a mid-frequency EQ to help you dial in your best sound. The focus mode provides two monitor signatures in one; 2-way monitor and 1-way full-range monitor from the woofer alone. The monitor is magnetically shielded for safe use near