Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

FOCAL TWIN6 ST6 RED (komad)- aktivni studijski monitor

Šifra: 16631
Kategorija prozivoda: Studijski monitori
Proizvođač: Focal

Cena: 1.886,00 EUR



Each driver is powered by its own amplifier for a total of 190W of RMS power for a strong and distortion-free performance. The rear panel offers a standard XLR input connector, which allows you to connect virtually any professional sound system. It also has a high-pass filter, shelving EQs for low and high frequencies, and a mid-frequency EQ to help you dial in your best sound. The focus mode provides two monitor signatures in one; 2-way monitor and 1-way full-range monitor from the woofers alone. The monitor is magnetically shielded for safe use near video monitors and other electronic equipment.

Beryllium inverted dome tweeter: exceptionally low directionality, excellent linearity and dynamics
Optimized baffle tweeter: excellent dispersion control
Composite sandwich W-cone: sound neutrality, no distortion
Focus mode: two monitors in one; 2-way monitor and 1-way full-range monitor (woofer alone)
Large laminar port: no port noises or distortion
Automatic standby mode for saving power
Settings: LF shelving, HF shelving, LPF at 160 Hz

Focal Dual Specs
Studio Monitor
Monitor Type Active 2-Way
Enclosure Bass-Reflex, Shielded
Power Rating 190 W RMS
Drivers HF Driver: 1 x 1.5" / 3.8 cm Beryllium Inverted Dome Tweeter
LF Driver: 2 x 6.5" / 16.5 cm Composite Cone
Amplification 1 x HF Amplifier: Rated at 50 W RMS
2 x LF Amplifier: Rated at 70 W RMS
Performance
Frequency Response 45 Hz to 40 kHz ± 3 dB
Maximum Sound Pressure Level (SPL) 112 dB
Analog Input Sensitivity/Gain +4 dBu / -10 dBV (Fixed)
Phase Adjustment None
Protections and Limiting Fuse
Signal Processing
EQ 1 x Low-Mid Shelf: -3 to +3 dB at 250 Hz (Continuously Variable dB Increments)
1 x Mid Notch/Peak: -3 to +3 dB at 160 Hz (Continuously Variable dB Increments)
1 x HF Shelf: -3 to +3 dB at 4.5 kHz (Continuously Variable dB Increments)
Filters 1 x High-Pass at 45 to 90 Hz
Parametric EQ None
Connectivity
Audio I/O 1 x XLR Balanced Analog Input (10 Kilohms)
Power

AC Input Power 100 to 240 VAC, 50/60 Hz
General
Enclosure Material MDF
Dimensions (W x H x D) 20.2 x 10.2 x 13.5" / 51.4 x 25.8 x 34.4 cm
Weight 48.5 lb / 22.0 kg
Packaging Info
Package Weight 53 lb
Box Dimensions (LxWxH) 26.38 x 19.75 x 17"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.