

FOCAL SUB12 ST6 RED - aktivni subwoofer

Šifra: 16632

Kategorija proizvoda: Studijski monitori

Proizvođač: Focal

Cena: 2.629,00 EUR

FOCAL SUB12 ST6 RED aktivni subwoofer

The

Sub12 has right, left, and LFE balanced XLR inputs for connecting to pro-level audio systems, while the right, left, and LFE balanced outputs allow you to connect satellites and additional subwoofers. It also has a 1/4" footswitch input that allows you to connect a pedal for hands-free control of the subwoofer. Signal treatment and control options include mono left/right summation, phase adjustment, polarity switch, high/low pass filters, level control, muting, and bypass.

Provides bass reinforcement for the Solo6 and Twin6 studio monitors

13" W-composite sandwich cone driver is housed in a high-volume MDF cabinet

Amplification: 600W RMS, 1000W peak

Large laminar bass port, which helps extend bass while reducing noise and distortion

Right, left, and LFE balanced XLR inputs for connecting to pro-level audio systems

Right, left, and LFE balanced XLR outputs for connecting to satellites and additional subs

1/4" footswitch input allows you to connect a pedal for hands-free control

Signal treatment and control options include mono left/right summation, phase adjustment, polarity switch, high-/low-pass filters, level control, muting, and bypass

Integrated carrying handle

Focal SUB12 Specs

Studio Monitor

Monitor Type Active 2-Way

Enclosure Bass-Reflex, Shielded

Power Rating 600 W RMS

1000 W Peak

Drivers LF Driver: 1 x 13" / 33 cm Composite Cone

Amplification 1 x LF Amplifier: Rated at 600 W RMS / 1000 W Peak

Performance

Frequency Response 30 Hz to 400 Hz \pm 3 dB

Maximum Sound Pressure Level (SPL) 124.5 dB

Analog Input Sensitivity/Gain +4 dBu / -10 dBV (Fixed)

Phase Adjustment 0 to 180° Continuous Phase Control

Protections and Limiting Fuse

Signal Processing

EQ None

Filters 1 x High-Pass at 45 to 90 Hz

1 x Low-Pass at 50 to 150 Hz

Parametric EQ None

Connectivity

Audio I/O 2 x XLR Balanced Female Analog Input (10 Kilohms)

4 x XLR Balanced Male Analog Output/Thru (50 Kilohms)

Power

AC Input Power 100 to 240 VAC, 50/60 Hz

General

Enclosure Material MDF

Dimensions (W x H x D) 19.2 x 23.6 x 22.4" / 48.7 x 60 x 56.8 cm

Weight 127.8 lb / 58.0 kg

Packaging Info

Package Weight 140 lb

Box Dimensions (LxWxH) 30.25 x 28.25 x 23.88"