Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

FOCAL SUB12 ST6 RED - aktivni subwoofer

Šifra: 16632
Kategorija prozivoda: Studijski monitori
Proizvođač: Focal

Cena: 2.337,00 EUR



The

Sub12 has right, left, and LFE balanced XLR inputs for connecting to pro-level audio systems, while the right, left, and LFE balanced outputs allow you to connect satellites and additional subwoofers. It also has a 1/4" footswitch input that allows you to connect a pedal for hands-free control of the subwoofer. Signal treatment and control options include mono left/right summation, phase adjustment, polarity switch, high/low pass filters, level control, muting, and bypass.

Provides bass reinforcement for the Solo6 and Twin6 studio monitors
13" W-composite sandwich cone driver is housed in a high-volume MDF cabinet
Amplification: 600W RMS, 1000W peak
Large laminar bass port, which helps extend bass while reducing noise and distortion
Right, left, and LFE balanced XLR inputs for connecting to pro-level audio systems
Right, left, and LFE balanced XLR outputs for connecting to satellites and additional subs
1/4" footswitch input allows you to connect a pedal for hands-free control
Signal treatment and control options include mono left/right summation, phase adjustment, polarity switch, high-/low-pass filters, level control, muting, and bypass
Integrated carrying handle

Focal SUB12 Specs
Studio Monitor
Monitor Type Active 2-Way
Enclosure Bass-Reflex, Shielded
Power Rating 600 W RMS
1000 W Peak
Drivers LF Driver: 1 x 13" / 33 cm Composite Cone
Amplification 1 x LF Amplifier: Rated at 600 W RMS / 1000 W Peak
Performance
Frequency Response 30 Hz to 400 Hz ± 3 dB
Maximum Sound Pressure Level (SPL) 124.5 dB
Analog Input Sensitivity/Gain +4 dBu / -10 dBV (Fixed)
Phase Adjustment 0 to 180° Continuous Phase Control
Protections and Limiting Fuse
Signal Processing
EQ None
Filters 1 x High-Pass at 45 to 90 Hz
1 x Low-Pass at 50 to 150 Hz
Parametric EQ None
Connectivity
Audio I/O 2 x XLR Balanced Female Analog Input (10 Kilohms)
4 x XLR Balanced Male Analog Output/Thru (50 Kilohms)

Power
AC Input Power 100 to 240 VAC, 50/60 Hz
General
Enclosure Material MDF
Dimensions (W x H x D) 19.2 x 23.6 x 22.4" / 48.7 x 60 x 56.8 cm
Weight 127.8 lb / 58.0 kg
Packaging Info
Package Weight 140 lb
Box Dimensions (LxWxH) 30.25 x 28.25 x 23.88"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.