Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

Reloop RP-7000 MK2 Silver - DJ gramofon



Šifra: 13588
Kategorija prozivoda: DJ gramofoni
Proizvođač: Reloop

Cena: 559,00 EUR

Napomena: Uz gramofon se ne dobiva igla!

STURDY CASING CONSTRUCTION

By using a combination of metal, rubber and synthetic materials, the RP-7000 MK2's housing is more reinforced and heavy than ever before. This results in a turntable that is extremely resistant to vibrations that can be caused by heavy bass sounds in DJ booths and its shock-absorbing feet help to further improve isolation. The surface is coated with a scratch-resistant high-quality deep black or classic silver metalic finish.

BALANCED S-SHAPED TONE ARM WITH UPGRADED TONE ARM BASE

The RP-7000 MK2 features a statically balanced S-shaped tone arm with hydraulic lift and anti-skating mechanism. The newly developed tone arm base provides improved stability and adjustable height/vertical tracking angle (VTA). The low-resonance tone arm comes with a universal connection for pick-up cartridge systems (SME).

DUAL START/STOP BUTTONS, PRECISE MOTOR CONTROL AND REVERSE FUNCTION

As well as the above technical innovations, the RP-7000 MK2 is equipped with a few functions that will make any DJ's life much easier. The newly developed aluminium LED target light is freely moveable to help you find the stylus position in dark surroundings. The target light is also removable and easily exchanged. An additional start/stop button has also been integrated to facilitate a vertical setup (battle position) and by using the buttons on the RP-7000 MK2's top panel, you can switch between the three motor speeds (33 1/3, 45 & 78 rpm). Dedicated buttons for forward and reverse mode allow for further creativity in your mix.

HIGH-RESOLUTION PITCH SECTION WITH DIGITAL FADER

Using the high-resolution pitch fader you can adjust the platter speed in the classic turntable pitch range +/-8%. However, the RP-7000 MK2 is also cable of a wider, DJ-friendly +/- 16% pitch range and a massive +/-50% ultra-pitch. This allows for increased creativity when modulating the playing record's tone. If quartz lock is active, the platter speed will remain unaffected by the fader position and will spin at zero pitch (0%).

HIGH-QUALITY CONNECTIONS AND INTEGRATED PHONO PRE-AMP

Thanks to the recessed rear connection panel, the RP-7000 MK2 can easily be mounted in a flight case and seamlessly positioned next to other DJ gear. The switchable integrated phono pre-amp makes it is possible to use the gold-plated RCA connectors for both phono and line output signals. An optional ground terminal offers additional protection in club environments. All cable connections (RCA/mains) are detachable and easy to exchange, which also helps with transport and storage.

POWERFUL MOTOR WITH EXTENSIVE ADJUSTMENT POSSIBILITIES

The fine-tuned, quartz-driven motor with digital pitch correction operates at a starting torque of 2.8kg/cm, which can be adjusted up to a maximum of 4.5kg/cm. This makes it an extremely smooth running turntable with wow and flutter of just 0.01% WRMS*. Furthermore, the turntable break speed (platter stop) can be adjusted from 0.2 – 6 seconds and the precision-machined, heavy die-cast aluminium platter is lined with vibration reducing rubber to eliminate unwanted vibrations and resonance.

RP-7000 MK2 SILVER

NextGen Turntable for professional Club DJs and Turntablists

Power-Torque Direct Drive with precise motor control and stable rotation

Extra-heavy body design with high-rigidity for excellent damping, isolation and sound

FEATURES

New features of the MK2 version:

Built for the club: rigid chassis construction with an even heavier design with additional reinforcements made of metal, rubber and molding compound for high vibration damping and isolation

More powerful starting torque (adjustable from 2.8 - 4.5 kg/cm)

Fine-tuned motor control for further optimization of wow and flutter and rotation

Newly developed, height-adjustable tone arm base (VTA) and anti-skating control

Particularly lightweight and rigid, satin aluminium material used for tone arm pipe

Pitch scale for precise adjustments

Optional ground terminal offers additional protection in complex club & studio environments

Easily replaceable, freely rotatable LED needle illumination in new unibody aluminium design

High-quality and hard-wearing silver metallic finish

Quartz driven DJ turntable with upper-torque direct drive

Adjustable brake speed (0.2 - 6 sec.)

Precise control of motor with 3 speeds (33 1/3, 45 & 78 rpm)

Precision manufactured, die cast aluminium turntable

Rubber inlays for reduction of vibrations and background noise

Statically-balanced universal S-shaped tone arm with hydraulic lift and anti-skating mechanism

Universal connection for pick-up systems (SME)

Pitch range +/-8 %, +/-16 %, +/-50 % (ultra pitch)

Quartz lock

Additional start/stop button for vertical positioning

Reverse function: switch for forward and reverse playback

Recessed connection cavity for easy flight-case installation & seamless adjustment

Phono and line out (no grounding required)

Removable mains and RCA cables

Safety mains switch

Shock-absorbing feet against vibrations

Incl. turntable, slipmat, LED needle light, counterweight, Phono RCA cable with earth, power cord, operating instructions

Start-up time / change to RPM:
<0.2 sec

Wow and flutter: 0.01% WRMS*

S/N ratio: > 55dB (DIN-B)

Brake system: electronic brake

Record weight: recommended
800g

Platter:

Material: die cast aluminium

Diameter: 332 mm

Weight: approx. 1.5 kg

Tone arm:

Type: universal, statically balanced, S-shaped

Effective length: 230 mm

Overhang: 15 mm

Tracking error range: < 3°

Offset Angle: 22°

Stylus Pressure: 0 - 4 g

VTA setting range: 0-6 mm

Useable weight of pick-ups: 3.5~8.5 g (incl. headshell 13~18 g)

Anti-skating range: 0 – 3 g

Effective tone arm mass: 12.8 g
(incl. headshell)

Connections:

1x Phono/Line Out (gold-plated),
1x GND earth connection

General:

Power supply: AC 115/230 V,
60/50 Hz (EU/US), AC 100 V,
50/60 Hz (JP)

Power consumption: 13 W

Dimensions: 458 x 144.6 x 354
mm

Weight: approx. 11.7 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.