

MACKIE EM-89D - dinamički vokalni mikrofon

Šifra: 15484

Kategorija proizvoda: Dinamički

Proizvođač: MACKIE

Cena: 45,00 EUR



The
EM-
89D

utilizes a cardioid polar pattern, which rejects sound behind the mic to reduce the pickup of stage bleed and allow higher gain before feedback. The mic's dynamic moving-coil design requires no batteries or phantom power, and the balanced 3-pin XLR output ensures proper connectivity with stage boxes, mixers, and portable PA systems. The EM-89D includes a mic clip, an XLR cable, and a zipper pouch.

Mackie EM-89D Specs

Microphone

Form Factor Handheld / Stand/Boom Mount

Sound Field Mono

Operating Principle Pressure Gradient

Capsule 1 x Dynamic

Polar Pattern Cardioid

Orientation End Address

Circuitry Solid-State

Pad None

High-Pass Filter None

Tone Adjustment None

Indicators None

On-Board Controls None

Windscreen Built-In

Performance

Frequency Range 50 Hz to 16 kHz

Impedance 600 Ohms \pm 30% at 1 kHz

Sensitivity -52 dBV/Pa at 1 kHz

Connectivity

Output Connectors (Analog) 1 x XLR 3-Pin Male (on Mic)

Headphone Connector None

Number of Conductors 2

Power

Operating Voltage Not Specified by Manufacturer

Physical

Color Black

Mounting Mic Clip/Stand Adapter (Included)

Dimensions \varnothing : 2 x L: 7.3" / \varnothing : 5.08 x L: 18.54 cm

Weight 0.66 lb / 0.3 kg