

logo not found or type unknown

Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

NATIVE INSTRUMENTS TRAKTOR KONTROL S3 - DJ kontroler

Šifra: 13730
Kategorija proizvoda: DJ kontroleri
Proizvođač: Native Instruments

Cena: 463,00 EUR

NATIVE INSTRUMENTS TRAKTOR KONTROL S3 - DJ kontroler

SYSTEM REQUIREMENTS

macOS 10.15, 11, 12, 13, 14 (latest update), iTunes 12
GB RAM

Windows 10, 11 (latest service pack), Intel Core i5 or e

SUPPORTED AUDIO FORMATS

MP3, WAV, AIFF, Audio-CD, FLAC, Ogg Vorbis, non-DRM AAC

GENERAL

Monitor with 1280 x 800 screen resolution, USB 2.0, 1 GB free disc space. An internet connection and a graphics card which supports OpenGL 2.1 or higher are required to download and activate TRAKTOR software. Once installed and activated, all products can be used offline.

SUPPORTED DRIVERS

Core Audio, WASAPI, ASIO, DirectSound

HARDWARE SPECIFICATIONS

Audio	
Channels:	4 out / 2 in
Sample Rate / Resolution	44kHz/48kHz – 24-bit
Main Out (Balanced - XLR)	
Signal Level	18.7 dBu
THD+N	0.001%
Freq Resp	+/- 0.1 dB
Channel Separation L/R	<-107
Crosstalk	-106 dB
Dynamic Range	111 dB
Booth Out (Balanced - TRS)	
Signal Level	18.7 dBu
THD+N	0.009%
Freq Resp	+/- 0.1 dB

Channel Separation L/R	<-107
Crosstalk	-109 dB
Dynamic Range	111 dB
Main Out (Unbalanced - RCA)	
Signal Level	+12.8 dBu
THD+N	0.0009%
Freq Resp	+/- 0.1 dB
Channel Separation L/R	<-106 dB
Crosstalk	-105 dB
Dynamic Range	110 dB
Headphone Out @32 Ω (Stereo Unbalanced - TRS) with 12V PSU	
Signal Level	7.7 dBu
THD+N	0.015%
Freq Resp	+/- 0.1 dB
Channel Separation L/R	-65 dB
Crosstalk	<-105
Dynamic Range	109 dB
Headphone Out @32 Ω (Stereo Unbalanced - TRS) USB powered	
Signal Level	-16.5 dBu
THD+N	0.001%
Freq Resp	+/- 0.1 dB
Channel Separation L/R	64 dB
Crosstalk	<-81 dB

Dynamic Range	85 dB
Line In (Unbalanced - RCA)	
Signal Level	+13 dBu
THD+N	0.002%
Freq Response	+/- .1dB
Channel Separation L/R	100 dB
Dynamic Range	105 dB
Mic In (Balanced - XLR/TRS)	
Signal Level	-10 dBu
THD+N	0.002%
Freq Resp	+/- 0.03 dB
Dynamic Range	97 dB