Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

MACKIE EM-93MK - set za live stream

Šifra: 17103
Kategorija prozivoda: Studijska oprema i pribor
Proizvođač: MACKIE

Cena: 116,00 EUR



The condenser micro comes with two windscreens, furry and foam, while the LED video light includes a diffuser for adjusting light intensity and adding a nice soft glow to your shots. With three cold shoe mounts on the LED light, setup is easy, and the convenient LCD display lets you dial in the perfect light temperature based on your available ambient light.

Versatile and Simple
The EM-93MK kit is designed to take the hassle out of content creation so that you can simply grab your phone, some snacks, and focus on your work. In the box, you get the cardioid EM-93M ultracompact microphone with both furry and foam windscreens, a variable temperature LED video light with diffuser, universal phone mount, handheld tripod, extension pole, plus a carry bag. Not only does it work great on a desk, but it's also just as easy to take with you on the go, even handheld.

One Kit, Endless Content
Awesome audio, lighting, smartphone stand, good to go. All nestled neatly in their custom case. From yoga videos to live streams, its incredibly easy to get great sound and a good look with the EM-93MK vlogger kit. You can even adapt the LED light to the ambient light in the room with its variable color temperature. And the included diffuser adds a nice soft glow to your shot.

Mackie EM-93MK Specs
Microphone
Primary Applications Web-Streaming, Recording to Mobile Device, ENG (Electronic News Gathering), Audio for Video, Location Sound, Field Recording
Form Factor Camera-Mount / Mobile Device Mic
Intended Sound Sources Vocals, Speech/Voice Over, Room Ambiance
Sound Field Mono
Operating Principle Pressure Gradient
Capsule 1 x Condenser
Polar Pattern Cardioid
Orientation End Address
Circuitry Solid-State
Pad None
High-Pass Filter None
Tone Adjustment None
Gain Adjustment None
On-Board Controls None
Windscreen Windsock/Windjammer (Included)
Foam (Included)
Performance
Frequency Range 35 Hz to 20 kHz
Impedance 680 Ohms

Sensitivity -42 dB
Signal-to-Noise Ratio 68 dB
Connectivity
Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRS Female (on Mic)
1 x 1/8" / 3.5 mm TRS Male (on Detachable Cable)
1 x 1/8" / 3.5 mm TRRS Male (on Detachable Cable)
Headphone Connector None
Power
Operating Voltage Not Specified by Manufacturer
Physical
Color Black
Mounting Camera/Shoe-Mount (Included)
Mounting Thread Size Included Mount Has No Threading
Included Case None
Included Filters None
Certifications WEEE, ICES-003 (B), FCC Part 15
*as per Manufacturer
Dimensions H: 3.1 x W: 0.9" / H: 7.9 x W: 2.3 cm
Weight 1.4 oz / 40 g

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.