Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

MACKIE Thump 118S (komad) - aktivni subwoofer

Šifra: 17108
Kategorija prozivoda: Aktivni zvučnici
Proizvođač: MACKIE

Cena: 632,00 EUR



The Thump118S features two XLR line inputs, two high-pass XLR outputs, and two full-range XLR outputs. There is a variable crossover control, polarity invert, a defeatable front-panel LED, and mono/stereo summing for single- or dual-subwoofer deployment. Two cut-through handles are offered on the upper side of the enclosure for easy transport and lifting. An M20-threaded pole mount is included for raising your full-range speakers above the audience for proper deployment.

A True Workhorse for Gigging Professionals
1400W Class-D amplifier is designed for ultrareliable, consistent performance
18” high-performance woofer
Built-Like-A-Tank to conquer every gig while lightweight for easy loading
Frequency response: 30 to 150 Hz
Max SPL: 132 dB

Voicing Modes
Flat: Natural balance between deep bass and overall output
Deep: Emphasizes ultra-low frequencies. Great for dance, rap, and electronic music
Punch: Prioritizes highest possible output level. Great for bands and rock music
Variable

Optimized for Your System
Variable crossover frequency
Polarity invert switch
Defeatable front LED
Stereo or mono summing for single- or dual-subwoofer deployment
Variable level control (-6 to +6 dBu)
Front LED On/Off

Versatile Inputs and Outputs
Stereo XLR inputs
Stereo full-range XLR outputs
Stereo high-pass XLR outputs

Versatile Configuration Options
Integrated M20-threaded pole mount

Mackie Thump118S Specs
Configuration Active Subwoofer
Enclosure Type Bass-Reflex Subwoofer
Total Power Capacity 1400 W Peak

Amplifier Class Class-D
Drivers
MF Driver None
LF Driver 1 x 18" / 457.2 mm Woofer
Performance
Frequency Response 30 Hz to 150 Hz
Maximum SPL 132 dB SPL
Connectivity
Audio I/O 2 x XLR 3-Pin Female Balanced Line Input
4 x XLR 3-Pin Male Balanced Line Output
Network I/O None
USB None
Wireless Connectivity None
Signal Processing
Crossover High-Pass:
80 to 160 Hz
EQ None
Parametric EQ None
Semi-Parametric EQ None
Filters None
Alignment Delay None
Phase Adjustment -180 / 0°
Digital Signal Processing Voicing Modes
Power
AC Input Power Universal:
100 to 240 VAC, 50 / 60 Hz
AC Power I/O 1 x IEC
Power Consumption 75 W
Physical
Mounting 1 x M20 Pole Socket (Top)
Handles 1 x Each Side
Dimensions 24 x 21 x 20.8" / 609.6 x 533.4 x 528.3 mm
Weight 82 lb / 37.2 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.