Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

For

Mackie SRM150 (komad) - aktivni razglasni zvučnik



Šifra: 18527
Kategorija prozivoda: Aktivni zvučnici
Proizvođač: MACKIE

Cena: 214,00 EUR

Boardroom A/V to Live Music
- Portable Powered Loudspeaker System
- 3-Channel Mixer with 3-Band EQ
- Two Mic/Line Preamps with 48V
- Hi-Z Input for Instruments
- Dedicated Stereo Line-Level Channel
- Built-In Limiter for System Protection
- Mic Stand Integration System
- Lightweight at 7.6 lb
- Includes Power Cord

Key Specs

Speaker Configuration	1x Full-Range Loudspeaker
Number of Input Channels	3 (2 x Mono, 1 x Stereo)
Amplifier Power Rating	150 W

Audio I/O	1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input 1x Combo XLR-1/4" TRS Mic/Line Input 1x Combo XLR-1/4" TRS Line Input 1x Stereo RCA TS Input 1x XLR 3-Pin Male Mic/Line Thru

Portable PA System

Speaker Configuration	1x Full-Range Loudspeaker
Number of Input Channels	3 (2 x Mono, 1 x Stereo)
Amplifier Power Rating	150 W
Amplifier Class	Class-D

Speakers

Full-Range Driver	5.25" / 133.35 mm Cone
Magnet	Neodymium

Signal Processing

Input Pad	No
EQ	**Contour:** ±15 dB at 12 kHz (on Master) ±15 dB at 2.5 kHz (on Master) ±15 dB at 100 Hz (on Master)

Performance

Frequency Response	100 Hz to 17.5 kHz -3 dB

Frequency Range	60 Hz to 22 kHz -10 dB
Maximum SPL	120 dB (Peak)
I/O Impedance	**Mic Input:** 3 Kilohms (Balanced) **Hi-Z Input:** 20 Kilohms (Balanced) **Line Input:** 10 Kilohms (Balanced)
THD	0.05%
Protections	AC Fuse, Output Limiter

Connectivity

Audio I/O	1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input 1x Combo XLR-1/4" TRS Mic/Line Input 1x Combo XLR-1/4" TRS Line Input 1x Stereo RCA TS Input 1x XLR 3-Pin Male Mic/Line Thru
Phantom Power	+48 V (Switchable)

Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
AC Power I/O	IEC Input

Physical

Transport Options	Handle (Top)
Mounting	1 x Mic Stand Socket (Bottom)
Construction Material	Polypropylene
Environmental Protection	No

Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	11.2 x 8 x 6.8" / 28.4 x 20.3 x 17.3 cm
Weight	7.6 lb / 3.4 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.