

## Mackie SRM150 (komad) - aktivni razglasni zvučnik

Šifra: 18527

Kategorija proizvoda: Aktivni zvučnici

Proizvođač: MACKIE

**Cena: 296,00 EUR**



Boardroom A/V to Live Music

Portable Powered Loudspeaker System

3-Channel Mixer with 3-Band EQ

Two Mic/Line Preamps with 48V

Hi-Z Input for Instruments

Dedicated Stereo Line-Level Channel

Built-In Limiter for System Protection

Mic Stand Integration System

Lightweight at 7.6 lb

Includes Power Cord

### Key Specs

Speaker Configuration	1x Full-Range Loudspeaker
Number of Input Channels	3 (2 x Mono, 1 x Stereo)
Amplifier Power Rating	150 W

Audio I/O

1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input  
1x Combo XLR-1/4" TRS Mic/Line Input  
1x Combo XLR-1/4" TRS Line Input  
1x Stereo RCA TS Input  
1x XLR 3-Pin Male Mic/Line Thru

## Portable PA System

Speaker Configuration

1x Full-Range Loudspeaker

Number of Input Channels

3 (2 x Mono, 1 x Stereo)

Amplifier Power Rating

150 W

Amplifier Class

Class-D

## Speakers

Full-Range Driver	5.25" / 133.35 mm Cone
-------------------	------------------------

Magnet	Neodymium
--------	-----------

## Signal Processing

Input Pad	No
-----------	----

EQ	<b>Contour:</b> ±15 dB at 12 kHz (on Master) ±15 dB at 2.5 kHz (on Master) ±15 dB at 100 Hz (on Master)
----	--

## Performance

Frequency Response	100 Hz to 17.5 kHz -3 dB
--------------------	--------------------------

Frequency Range	60 Hz to 22 kHz -10 dB
Maximum SPL	120 dB (Peak)
I/O Impedance	<b>Mic Input:</b> 3 Kilohms (Balanced) <b>Hi-Z Input:</b> 20 Kilohms (Balanced) <b>Line Input:</b> 10 Kilohms (Balanced)
THD	0.05%
Protections	AC Fuse, Output Limiter

## Connectivity

Audio I/O	1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input 1x Combo XLR-1/4" TRS Mic/Line Input 1x Combo XLR-1/4" TRS Line Input 1x Stereo RCA TS Input 1x XLR 3-Pin Male Mic/Line Thru
Phantom Power	+48 V (Switchable)

## Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
AC Power I/O	IEC Input

## Physical

Transport Options	Handle (Top)
Mounting	1 x Mic Stand Socket (Bottom)
Construction Material	Polypropylene
Environmental Protection	No

Operating Temperature

32 to 104°F / 0 to 40°C

Dimensions

11.2 x 8 x 6.8" / 28.4 x 20.3 x 17.3 cm

Weight

7.6 lb / 3.4 kg