Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

SVS Ultra Elevation Piano Gloss White (pair) - HiFi zvučnik



Šifra: 19047
Kategorija prozivoda: Hi Fi Zvučnici
Proizvođač: SVS

Cena: 1.099,00 EUR

Frequency Response / Acoustic Data:

Frequency Response: 48Hz to 40kHz (+/-3 dB)
Nominal impedance: 6 ohms.

Sensitivity: 87 dB (2.83V @ 1 meter full-space, 300-3kHz)
Recommended amplifier power: 20-150 watts.

Speaker Specs:

Elevation Loudspeaker
Piano gloss black, piano gloss white, real black oak veneer finish options
Gold-plated 5-way binding posts
1.4” wide-flared rear-firing port
Cloth grille with magnetic retention system
Magnetic SVS Logo which can be removed and oriented according to speaker application
Elastomer stick-on bumper feet
Unique SVS Multi-Angle Wall Bracket system the allows speaker to be wall or ceiling mounted in. Magnetic ceiling lock included.
1/4-20" brass insert for use with included SVS Multi-Angle Wall Bracket and other bracket mounting systems.

Cabinet Dimensions: 11.14” (H) x 7.28” (W) x 8.79” (D) / 283mm (H) x 185mm (W) x 223.2mm (D)
Overall Dimensions: 11.14” (H) x 7.28” (W) x 9.82” (D) / 283mm (H) x 185mm (W) x 249.4mm (D) (includes grille and SVS Multi-Angle Wall Bracket)
Shipped Dimensions: 11.6” (H) x 20.9” (W) x 15” (D) / 295mm (H) x 532mm (W) x 381mm (D)
Weight Packaged: 27.8 pounds / 12.6 kgs
Weight Unboxed: 12.3 pounds / 5.6 kgs

Driver Specs:

1” Diamond Coated Tweeter

FEA-optimized Organic Cell Lattice Diffuser for airy, unveiled highs and pristine clarity.
Cutting-edge vapor-deposition grows a hyper-rigid diamond-like coating on an aircraft-grade aluminum dome, pushing high-frequency extension further beyond human hearing, and delivering best-in-class

fidelity, linearity, and transient response.
Silver tinsel leads for optimal signal transfer and power handling.

5.25” Woofer

Long stroke motor and suspension for high output.
Composite glass-fiber cone with excellent stiffness/mass ratio for high sensitivity and pistonic behavior beyond passband.
Precision-cast aluminum alloy baskets ensure precise alignment of critical components and maximize thermal dissipation.
Vented aluminum voice coil former to maximize thermal control while minimizing air compression artifacts at high drive levels.

Crossover & Cabinet Specs:

Crossover:

2-way crossover with premium-grade capacitors, inductors, resistors, and heavy-trace printed circuit board
Tweeter-to-woofer crossover: 1.9 kHz

Cabinet:

Chamfered front baffle and flush-mounted drivers reduce edge diffraction and improve on-axis and off-axis high-frequency response.
Extra-thick 1” (25mm) driver baffle ensures a rigid, resonance-free mounting for all drivers.
FEA-optimized ¾” (18mm) cabinet construction, bracing, and acoustic insulation eliminate acoustic and structural resonances, ensuring an inert enclosure and an uncolored response, even at the highest drive levels.
Angled baffle and optimized crossover combine for perfect acoustic performance at any position.

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.