Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

# SVS RCA Interconnect 2M - HiFi kabel

Šifra: 19068
Kategorija prozivoda: Hi Fi
Proizvođač: SVS

## Cena: 42,50 EUR




Premium RCA Cables

SVS SoundPath Stereo RCA Audio Cables let your system reach its full performance potential by ensuring pristine signal purity and rejecting interference. Connect your preamp, stereo subwoofers, DAC or other components and enjoy rich, detailed listening experiences.
Durable and Truthful Stereo RCA Cables

Multi-strand 99.99% pure copper conductors deliver ultra-high bandwidth and low capacitance for truthful audio signal rendering. With pure copper conductors, 24K gold plated brass connectors, and a precision-engineered five-layer dielectric insulation system, the cables ensure pristine sound while eliminating interference.

SVS SoundPath Stereo RCA Audio Cables are available in convenient lengths ranging from one to 15 meters and ensure secure and uncompromised audio connections.
Specifications

- Pristine signal transfer from pure copper center conductor and 24K gold plated brass connectors
- Precision-engineered five-layer dielectric insulation system
- Ultra-high bandwidth and ultra-low capacitance

**Cable - Materials of Construction:**

All new premium cotton braided jacket – attractive, durable, outermost boundary of five-layer dielectric insulation system
High density 7.0mm PVC outside core dielectric – part of five-layer insulation system
1.6mm HDPE inside core dielectric – part of five-layer insulation system, shields each unique conductor
PET Mylar shield layer – part of five-layer insulated system, shields and binds internal structure

Directional shield layer is a spiral braid of premium grade Aluminum foil and 56 strands of 99.99% OFC tinned copper Shielding – critical part of five-layer insulation system. Soldered to ground terminal at the source side helps reduce EMI and RF noise between electronics.
Total five-layer isolation system rejects electromagnetic (EM) and radio frequency (RF) interference.
The Dual balanced conductors are made from 14 strands of 99.99% OFC stranded copper conductors, and individually isolated in independent HDPE dielectric jackets - allow consistent signal flow, high signal purity, and minimize signal loss.
Nominal Cable Diameter: 7mm

**RCA Connector - Materials Of Construction:**

Precision soldered with high grade lead-free solder – Durable and consistent electrical contacts with consistent signal flow.

24K gold plated brass conductor pin – effective electrical contact and signal flow.
24K gold plated brass split grounding body – tight fit with consistent electrical contact for stable grounding.

Precision machined and anodized aircraft grade aluminum shell with white and red marking bands – Stylish and durable body with a great feel and easy handling. Red and White marking bands for easy Left and Right designation.
Center Pin and Outer Ring: Gold-plated brass for optimum signal quality and integrity.

**Electrical Properties:**

Conductor DCR = 77 mΩ/meter
Shield DCR: 30 mΩ/meter
Nominal Impedance: 110Ω. Cable and RCA connectors are impedance-matched to minimize Voltage Standing Wave Ratio (VSWR) and Return Loss.

Nominal Capacitance: 39 pF/meter @ 1kHz
Rated Bandwidth: DC-5.0 MHz (3M cable) with ≤1.09 VSWR and ≥27dB Return Loss

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.