


## Mackie SRT215 (komad) - aktivni razglasni zvučnik

Šifra: 18942

Kategorija proizvoda: Aktivni zvučnici

Proizvođač: MACKIE

**Cena: 830,00 EUR**



**Product:** SRT215

**Power:** 1600W

**LF Driver:** 15"

**HF Driver:** 1.4"

**Inputs:** Dual XLR/TRS

**Aux Inputs:** Stereo 1/8"

**Outputs:** XLR Direct Out per channel + Mix Out

**Frequency Response:** 42Hz - 20kHz

**Max SPL:** 133 dB

**App Control:** Yes

### **A True Workhorse for Gigging Professionals**

1600W Class-D amplifier is designed for ultra-reliable, consistent performance

Custom high-efficiency transducers ensure maximum clarity and accuracy

Built-Like-A-Tank™ to conquer every gig while lightweight for easy loading

Frequency response: 42Hz - 20kHz

Max SPL: 133 dB

Advanced Impulse™ DSP - Proprietary Acoustic Tuning

### **Crystal clear sound across the entire dispersion zone means the whole room is the sweet spot**

Precision crossover and transducer time-alignment ensures balanced and accurate sound

Custom Sym-X™ Horn

### **Allows for total efficiency from the HF transducer minimizing distortion and increasing output**

Creates a perfectly symmetrical, flat response at the crossover point for exceptionally smooth midrange

The horn-loading frequency is set below the HF drivers' LF capability allowing for maximum efficiency and

optimal performance at the crossover point

Coverage: 90° horizontal x 60° vertical

Transparent System Limiting and Protection

### **Dedicated processing module monitors and protects the amplifier in real time**

Sound quality and tonal balance is maintained even under heavy limiting

Utilizing powerful multi-band compression, the amplifier can target specific frequency ranges to prevent the system from being overloaded rather than turn everything down at the expense of overall output

Input limiting keeps your source signal in check so if you're sending audio that's a bit too hot, the speaker will cool it down

Universal Power Supply (100-240VAC) with Power Factor Correction for stable operation even with unstable AC power

SRT Mix Control™ Built-in 4-Channel Digital Mixer with Bluetooth®

### **Dual independent channels that support mic, line, and instrument signals**

Dedicated 1/8" stereo aux channel

Stream music from any Bluetooth® enabled device

High-contrast full color display for easy single-knob access to mixer and processing

Adjust channel levels and EQ

Application and venue specific voicing modes

Alignment delay - up to 100 feet

Save and recall up to 10 user presets

Screensaver plus dimmer and contrast control

System lock with 4-digit passcode

Front LED on, off and signal present modes

Complete Wireless Control via the SRT Connect™ App

### **The SRT Connect™ app gives you access to all adjustments and settings including EQ, levels, and presets**

Wirelessly link SRT speakers together for music streaming applications plus complete control over both speakers

### **The latest Bluetooth technology allows up to 100 meters of range between linked speakers**

Stereo or dual zone linking modes allows discrete control over the inputs and outputs of the entire system across two rooms or zones

Creates an incredibly clean setup in minutes

Versatile configuration options

### **Dual-angled cabinet design allows for use as a high-performance floor monitor**

Dual angle pole-mount provides optimal coverage and minimal reflections in most venues; 7-degree downward tilt is perfect for when the speakers are on elevated stages

M10 flypoints for professional installation

Weight: 37.1 lb / 16.8 kg

Dimensions: 28.8 x 17.6 x 15.4 in / 732 x 447 x 391 mm