

## Adam Audio T10s (komad) - aktivni subwoofer

Šifra: 19094  
Kategorija proizvoda: Studijski monitori  
Proizvođač: ADAM AUDIO

**Cena: 397,00 EUR**

### Adam Audio T10s (komad) - aktivni subwoofer

The T10S is a powerful yet compact active subwoofer, designed to extend the bass response of any nearfield studio monitor. However, the subwoofer's performance, features and connectivity are engineered specifically to complement ADAM Audio's T5V and T7V speakers.

Equipped with a down-firing 10" woofer and a 130 W Class-D amplifier, the T10S' frequency response ranges from 28 Hz to 120 Hz and offers an impressive max. SPL of 104 dB. An internal adjustable two-channel crossover allows calibration of the bass signal and provides optimal performance of the total system. The options at the rear of the subwoofer allow for varied adjustments which compensate for room acoustics or they offer more control for satellites attached.

While reciting the T Series design language, the T10S is one of the most compact subwoofers in its class, which allows it to be easily integrated in any studio environment. The acoustic performance was optimized by four high grade flexible rubber feet that prevent the sound from exciting the floor and a spacious rear facing bass reflex port for an optimized airflow.

### Features

#### Linear bass reproduction down to 28 Hz

Ideal addition to smaller nearfield monitors, specifically the T Series

#### Maximum Peak sound pressure in 1 m $\geq$ 104 dB

Powerful, compression-free sound reproduction even at very high sound levels

#### High efficiency PWM amplifier

Low-distortion amplification at both low and high volume levels

#### Special 10" woofer with paper diaphragm

Unrestricted bass reproduction for low-fatigue operation

#### Easy manual or automatic (de-)activation (via optional foot switch)

If desired, monitoring is possible without the low frequencies

### **Crossover optimized for T Series studio monitors**

Takes into account the specific characteristics of the T5V and T7V studio monitors for the best result

### **Analog XLR / RCA in- and outputs**

Optimized for balanced and unbalanced line signals

### **Small footprint**

Flexible positioning in room for optimal sound results

### **2 years warranty with optional extension to 3 years with the registration of the product**

Full repair service if required for 5 years

## **Technical specification**

### **SUBWOOFER (DOWN-FIRING)**

Basket Ø - 10" (260 mm)

Voice Coil Ø - 38mm / 1.5"

Cone Material - Paper

### **BUILT-IN AMPLIFIERS**

Subwoofer - 1

Type - PWM

Amp. Power RMS - 130 W

### **CONTROL PANEL**

Crossover Frequency - 80 Hz / 120 Hz / Bypass

Phase Inversion - 0° / 180°

## CONNECTORS

Analog Inputs - XLR / RCA

Analog Outputs - XLR / RCA

## GENERAL DATA

Frequency Response - 28 Hz - 120 Hz (@ -6 dB)

THD > 60 Hz - 0.6%

Max. SPL at 1 m (hemisphere) -  $\geq 104$  dB

Max. Power Consumption - 190 W

Input Sensitivity - +4 dBu / -10 dBV

Panel - Rear

Bypass - Yes, via footswitch (not included)

Standby - Yes, activates after 15 minutes with no incoming signal

Weight - 27 lb (12.2 kg)

Height x Width x Depth - 15.4" (390 mm) x 12.5" (318 mm) x 16.25" (413 mm)

Warranty - 5 years (2 years warranty plus 3 years optional with product registration) (2 years warranty plus 3 years optional with product registration)

Delivery Contents - Power cord, Quick Start Guide, Welcome Card