Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

MARTIN AUDIO X8B Black (komad) - pasivni zvučnik



Šifra: 13945
Kategorija prozivoda: Pasivni zvučnici
Proizvođač: Martin Audio

Cena: 399,00 EUR

Features
Ultra-Compact passive two-way system
Symmetrical multi-angle plywood enclosure
User-rotatable 90° x 50° horn
Vertical and horizontal orientation
Screw-free, cloth-backed perforated steel grille
Integral ergonomic handle
Pole-mount bung maintains clean lines
8Ω nominal impedance
Twin NL4 connectors
Flexible mounting options via M8 inserts

Applications
Portable sound reinforcement
Live music clubs
Bars and restaurants
Nightclubs
Unobtrusive stage monitoring
Corporate AV events and conferences
Weddings and parties
Main PA infill
Secondary stages at festivals
HoW, leisure centres and retail outlets

As a stand-alone loudspeaker, it has a multitude of professional applications — from distributed sound reinforcement, HoW and AV events to frontfill/infill and use as a micro stage monitor. Complemented by a BlacklineX subwoofer, it is the ideal, simple-to-use system for portable applications and installations which call for an unobtrusive system that can deliver pristine sound over short and medium throw distances.

The Blackline X8 is constructed from plywood and fitted with a screw-free steel grille, M8 inserts for wall brackets and eyebolt suspension, plus a pole-mount socket with a removable bung that maintains clean lines in install applications. Finished in black textured paint.

A full-range passive two-way system, the X8 may be used without a controller. However, the EQ and limiter functions of a controller such as the Martin Audio DX0.5 will maximise its capabilities. When used in conjunction with an X115, X118 or X210 subwoofer, crossover and EQ functions can be performed by the DX0.5.

TYPE Ultra-Compact, passive two-way system
FREQUENCY RESPONSE (5) 70Hz-20kHz ± 3dB, -10dB @ 60Hz
DRIVER LF: 8” (200mm)/2” (50mm) voice coil, ferrite motor system
HF: 1” (25mm) exit/1” (25mm) voice coil, polyimide dome compression driver
RATED POWER (2) 200W AES, 800W peak
SENSITIVITY (8) 92dB
MAXIMUM SPL (9) 115dB continuous, 121dB peak
NOMINAL IMPEDANCE 8Ω
DISPERSION (-6DB) 90° H x 50° V (user-rotatable)
CROSSOVER 2.9kHz passive
ENCLOSURE Multi-angle birch/poplar ply
FINISH Black textured paint
PROTECTIVE GRILLE Black perforated steel with scrim cloth backing
CONNECTORS 2 x NL4 type
PIN CONNECTIONS (INPUT) 1+/1-
PIN CONNECTIONS (LINK) 1+/- to 1+/-
FITTINGS 13 x M8, 6 x M6 inserts, pole-mount socket, 1 x pocket handle
DIMENSIONS (W) 257mm x (H) 422mm x (D) 243mm
(W) 10.1ins x (H) 16.6ins x (D) 9.6ins
WEIGHT 8kg (17.6lbs)
ACCESSORIES Wall bracket, eyebolts

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.