

MARTIN AUDIO BLACKLINE X10 - pasivni zvučnik

Šifra: 12365

Kategorija proizvoda: Pasivni zvučnici

Proizvođač: Martin Audio

Cena: 750,00 EUR



**Martin
Audio**

Blackline X10

The loudspeaker shall be a passive, two-way system. Its transducers shall consist of a reflex-loaded 10" low frequency driver and a 1.4" diaphragm/1" exit compression driver mounted on a high frequency horn which shall be user-rotatable to enable vertical or horizontal orientation of the enclosure.

Horizontal dispersion shall be 90° and vertical dispersion shall be 50°. The on-axis frequency response shall be 65Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 124dB peak calculated at 1 metre. Power handling shall be 250W AES, 1000W peak. Rated impedance shall be 8 ohms.

The rear connector panel shall be fitted with two NL4 type connectors. Low and high frequency sections shall be integrated by an internal 2.4kHz passive network. For optimal performance the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The symmetrical, multi-angle enclosure shall be made from plywood and finished with a black textured paint. Optional white and RAL colour finishes shall be available to special order. The enclosure shall be fitted with a pole-mount socket and M8 threaded inserts to accommodate eyebolt suspension and a wall bracket. The drivers shall be protected by a perforated steel grille with scrim cloth backing.

Dimensions (W x H x D) shall be 324mm x 522mm x 289mm (12.8in x 20.6in x 11.4in). Weight shall be 14kg (30.9lbs).

The loudspeaker shall be the Martin Audio Blackline X10.

Features

- Compact passive two-way system
- Symmetrical multi-angle plywood enclosure
- User-rotatable 90° x 50° horn
- Vertical and horizontal orientation
- Screw-free, cloth-backed perforated steel grille
- Integral ergonomic handle
- Pole-mount bung maintains clean lines
- 8Ω nominal impedance
- Twin NL4 connectors
- Flexible mounting options via M8 inserts

Applications

- Portable sound reinforcement
- Live music clubs
- Bars and restaurants
- Nightclubs

Unobtrusive stage monitoring
Corporate AV events and conferences
Weddings and parties
Main PA infill
Secondary stages at festivals
HoW, leisure centres and retail outlets

TYPE	Compact, passive two-way system
FREQUENCY RESPONSE (5)	65Hz-20kHz \pm 3dB, -10dB @ 55Hz
DRIVER	LF: 10" (250mm)/2.5" (63.5mm) voice coil, ferrite motor system HF: 1" (25mm) exit/1.4" (35mm) voice coil, polyimide dome compression driver
RATED POWER (2)	250W AES, 1000W peak
SENSITIVITY (8)	94dB
MAXIMUM SPL (9)	118dB continuous, 124dB peak
NOMINAL IMPEDANCE	8 Ω
DISPERSION (-6DB)	90° H x 50° V (user-rotatable)
CROSSOVER	2.4kHz passive
ENCLOSURE	Multi-angle birch/poplar ply
FINISH	Black textured paint
PROTECTIVE GRILLE	Black perforated steel with scrim cloth backing
CONNECTORS	2 x NL4 type
PIN CONNECTIONS (INPUT)	1+/1-
PIN CONNECTIONS (LINK)	1+/- to 1+/-
FITTINGS	19 x M8 inserts, pole-mount socket, 1 x bar handle
DIMENSIONS	(W) 324mm x (H) 522mm x (D) 289mm (W) 12.8ins x (H) 20.6ins x (D) 11.4ins
WEIGHT	14kg (30.9lbs)
ACCESSORIES	Wall bracket, eyebolts

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.