

Reloop RP-7 - DJ gramofon

Šifra: 20097

Kategorija proizvoda: DJ gramofoni

Proizvođač: Reloop

Cena: 449,00 EUR



Features

Industry-first, series-manufactured, professional 7" direct-

drive DJ turntable system

Quartz-controlled 7" turntable with high-torque direct-drive motor

Exclusively developed for the 45s DJ and vinyl enthusiast scene

Newly developed brushless DC motor with 2.5 kg/cm torque

Powerful torque for reliable vinyl cueing and advanced scratching techniques

Solid construction with a refined chassis and superior tonearm design

Precision-machined, die-cast aluminium platter

Finely tuned motor characteristics to minimise wow and flutter

Height-adjustable VTA tonearm base from the best-selling RP-7000/8000 series

Straight copper tonearm with internal rubber damping for superior vinyl tracking and minimal resonance

Statically-balanced, straight tonearm system with hydraulic lift, eliminating the need for anti-skating

Universal cartridge system connection (SME, headshell cartridges recommended)

Precise motor control with three speeds (33 1/3, 45 and 78 RPM)

Clickless tempo fader and adjustable tempo range supporting +/-8 %, +/-16 % or +/-35 %

Pitch reset toggle button and clearly indicated tempo scale

Recessed connection terminal for a flush setup

Gold-plated phono and line output

Newly developed internal switching power supply to reduce unwanted interference

Aluminium vinyl puck adapter with recessed storage slot

Strobe light indicator for all turntable speed settings

IEC connection with detachable mains and RCA cables

Detachable and freely rotatable LED needle illuminator in unibody aluminium design

Robust construction and high-quality finish in deep black metallic

Incl. turntable platter, vinyl puck, slipmat, slip sheet, LED needle light, counterweight, phono RCA cable with grounding, mains cable and instruction manual, (headshell and cartridge sold separately)

Technical Data

Turntable:

Type: 3-speed fully manual

Drive: Direct drive

Motor: 8-pole, 3-phase, high-torque brushless DC motor

Speeds: 33 1/3, 45, 78 RPM

Pitch: ±8, 16, 35%

Starting Torque: 2.5 kgf/cm (starting at 78 rpm)

Start-Up Time: < 1 sec.

Brake System: Electronic brake

Platter:

215 mm dia. die-cast aluminium

Tonarm:
Type: Static balanced straight-shaped tonearm
Overhang: 0 mm
Offset Angle: 9,5°
VTA setting range: 0 - 6 mm
Effective Tonearm Length: 164.5 mm
Wow and Flutter: Less than 0.15% WTD at 3 KHz RMS
S/N Ratio: More than 75 dB (A-w./20 KHz LPF)
Applicable Cartridge Weight: 15 ~ 20 g (including headshell)
Connections:
1x Phono/Line Out (gold-plated), 1x GND earth connection
General:
Power Input: AC 100-240 V, 50/60 Hz
Power Consumption: 3 W
Dimensions: 350(W) x 270(D) x 139(H) mm
Weight: 5.7 kg
Incl. turntable platter, vinyl puck, slipmat, slip sheet, LED needle light, counterweight, phono RCA cable with grounding, mains cable and instruction manual, (headshell and cartridge sold separately)