

Neutrik NL4FXX-W-S

Product

Šifra: 18148

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Connector series

Cena: 6,50 EUR

NL4FX:

speakC



Electrical

Contact resistance $\leq 2 \text{ m}\Omega$

Dielectric strength 2.8 kVac

Insulation resistance $> 10 \text{ G}\Omega$ (initially)

Number of electrical contacts 4

Rating Europe IEC 61984: 37 A 250 V AC

Rating USA UL1977: 35 A 250 V AC

Rating Canada CSA C22.2 No.182.3: 24 A 250 V AC

ATTENTION:

This product is strictly not intended for use as an AC mains or power supply connector!
CAUTION: NOT FOR INTERRUPTING CURRENT

Mechanical

Cable O.D. 6 - 12 mm

Lifetime typically 5'000 mating cycles

Wiresize (mm²) 1.5 - 4 mm²

Wiresize (AWG)	17 - 11 AWG
Locking device	Twist lock
Termination	screw type terminals

Material	
Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

Environmental	
Temperature range	-33 °C to +80 °C
Protection class	IP20
Flammability acc. to UL94	V-0