

Audient iD4 mk2 - zvučna kartica

Šifra: 18438

Kategorija proizvoda: Zvučne kartice

Proizvođač: Audient

Cena: 153,00 EUR



D.I / Instrument Input

Microphone Preamplifier

RANGE:40dB

LINEUP:12dBu = 0dBFS

THD+N @ 0dBu:0.1%

SNR:100dBu A-Weighted

FREQUENCY RESPONSE – MIN GAIN:±0.5dB 10Hz to 20kHz GAIN RANGE: 58dB

LINEUP:12dBu = 0dBFS

MIC MAX INPUT LEVEL:12dBu

LINE MAX INPUT LEVEL:21dBu

INPUT IMPEDANCE (Mic):2.8k

INPUT IMPEDANCE (Line):>8k

PHANTOM POWER: (48V +/-4V @ 10mA/Channel)

THD+N @ 0dBu:0.00170%

THD+N @ 0dBu MAX GAIN:<0.04%

SNR:101dBu A-Weighted

EIN:129dB A-Weighted

CMRR @ 1k:>75dB

Analogue to Digital Converter

FREQUENCY RESPONSE - MIN GAIN:±0.5dB 10Hz to 40kHz

THD+N @ -1dBFS:0.001%

DYNAMIC RANGE:120dB A-Weighted

FREQUENCY RESPONSE:±0.5dB 10Hz to 40kHz

Line Outputs (DAC)

LINEUP:12dBu = 0dBFS

THD+N @ -1dBFS:0.0006%

DYNAMIC RANGE:125.5dB A-Weighted

CROSSTALK:>120dB

Headphone Outputs

FREQUENCY RESPONSE:±0.1dB 10Hz to 40kHz

1/4" TRS JACK:Tip (Hot), Ring (Cold) & Sleeve (Shield)

LINEUP:18dBu = 0dBFS

THD+N @ -1dBFS:0.0009%

DYNAMIC RANGE:125.5dB A-Weighted

CROSSTALK:>116dB

FREQUENCY RESPONSE:±0.1dB 10Hz to 40kHz

MAXIMUM LEVEL @ 30R:2.59V Peak, 1.827V RMS, 223mW

MAXIMUM LEVEL @ 62R:4.18V Peak, 2.95V RMS, 280mW

MAXIMUM LEVEL @ 600R:7.72V Peak, 5.46V RMS, 100mW

1/4" TRS JACK:Tip (Left), Ring (Right) & Sleeve (Shield)

USB-C High Speed

BUS POWER:

MIN REQUIREMENT:0.9A @ 5V >=USB 3.0 Port

MAX REQUIREMENT:1.5A @ 5V USB-C: Provides hig

No. of INPUT CHANNELS:2 (2 Analogue)

No. of OUTPUT CHANNELS:2 (2 Analogue)

DSP MIXER LATENCY ROUND TRIP (in-to-out):44.1kHz 0.65mS

DSP MIXER LATENCY ROUND TRIP (in-to-out):48.0kHz 0.6mS

DSP MIXER LATENCY ROUND TRIP (in-to-out):88.2kHz 0.33mS

DSP MIXER LATENCY ROUND TRIP (in-to-out):96.0kHz 0.31mS