

logo not found or type unknown

Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

Audient EVO 4 - zvučna kartica

Šifra: 18443
Kategorija proizvoda: Zvučne kartice
Proizvođač: Audient

Cena: 117,00 EUR

Audient EVO 4 - zvučna kartica

Microphone Preamplifier

| | |
|-------------------------|--|
| Mic Gain Range: | 58dB |
| Line Gain Range: | 58dB (-10dB pad) |
| Phantom Power: | 48v +/-4v @ 10mA/Channel |
| Mic EIN: | <-128dBu |
| CMRR: | >85dB @ 1kHz |
| Maximum Input Level: | +16dBu |
| Input Impedance (Mic): | >3kΩ Balanced |
| Input Impedance (Line): | >10kΩ Balanced |
| Frequency Response: | +/-0.5dB 10Hz to 40kHz |
| Crosstalk: | <-105dBu @ 1kHz & 10kHz |
| THD+N @ 0dBu (1kHz): | <0.0015% |
| SNR: | 100dB |
| XLR: | Pin 2 (Hot), Pin 3 (Cold) & Pin 1 (Shield) |
| 1/4" Jack: | TIP (Hot), RING (Cold) & SLEEVE (Shield) |

D.I

| | |
|-----------------|-------|
| D.I Gain Range: | 58 dB |
|-----------------|-------|

| | |
|----------------------|--------|
| Maximum Input Level: | +10dBu |
|----------------------|--------|

| | |
|------------------|--------------------------|
| Input Impedance: | 1Meg Ω Unbalanced |
|------------------|--------------------------|

| | |
|--------------------|------------------------|
| Frequency Response | +/-0.5dB 10Hz to 20kHz |
|--------------------|------------------------|

| | |
|----------------------|-------|
| THD+N @ 0dBu (1kHz): | <0.3% |
|----------------------|-------|

ADC Inputs

| | |
|------|-------|
| SNR: | 100dB |
|------|-------|

| | |
|------------|-----------------------------|
| 1/4" Jack: | TIP (Hot) & SLEEVE (Shield) |
|------------|-----------------------------|

| | |
|--------------------------|---------------|
| Digital Reference Level: | 0dBFS = +8dBu |
|--------------------------|---------------|

| | |
|---------------------|-----------------------|
| Frequency Response: | +/-0.5dB 10Hz to Fs/2 |
|---------------------|-----------------------|

| | |
|------------|--------------------|
| Crosstalk: | -105dBu @ 1kHz & 1 |
|------------|--------------------|

| | |
|------------------------|---------|
| THD+N @ -1dBFS (1kHz): | <0.001% |
|------------------------|---------|

| | |
|----------------|------------------|
| Dynamic Range: | 113dB A-weighted |
|----------------|------------------|

DAC Outputs

| | |
|-----------------------|--------|
| Maximum Output Level: | +11dBu |
|-----------------------|--------|

| | |
|--------------------------|----------------|
| Digital Reference Level: | 0dBFS = +11dBu |
|--------------------------|----------------|

| | |
|-------------------|------------------------|
| Output Impedance: | <100 Ω Balanced |
|-------------------|------------------------|

| | |
|---------------------|-----------------------|
| Frequency Response: | +/-0.5dB 10Hz to Fs/2 |
|---------------------|-----------------------|

| | |
|------------|-----------------|
| Crosstalk: | <-110dBu @ 1kHz |
|------------|-----------------|

| | |
|------------------------|----------|
| THD+N @ -1dBFS (1kHz): | <0.0015% |
|------------------------|----------|

| | |
|----------------|------------------|
| Dynamic Range: | 113dB A-weighted |
|----------------|------------------|

| | |
|------------|--|
| 1/4" Jack: | TIP (Hot), RING (Cold) & SLEEVE (Shield) |
|------------|--|

Headphone Output

| | |
|-------------------------|-----------------|
| Output Impedance: | <50Ω |
| Frequency Response: | +/-0.5dB 10H |
| Crosstalk: | -110dBu @ 1K |
| THD+N @ -1dBFS (1kHz): | <0.0015% |
| Dynamic Range: | 113dB A-weig |
| Max Level Into 30ohms: | +0.5dBu, 0.0 |
| Max Level Into 60ohms: | +4.22dBu, 0. |
| Max Level Into 600ohms: | +10.1dBu, 0. |
| 1/4" Jack: | TIP (Left), RIN |

DSP Mixer Roundtrip Lat

(in to out)

| |
|----------|
| 44.1 kHz |
|----------|

| |
|----------|
| 48.0 kHz |
|----------|

| | |
|----------|---------|
| 88.2 kHz | 0.302ms |
|----------|---------|

| | |
|----------|---------|
| 96.0 kHz | 0.281ms |
|----------|---------|

DAW Playback Latency

@ 32 Sample Buffer for Software Instrument Playback

Latency - p
including CF

| | |
|----------|--------|
| 44.1 kHz | ~2.5ms |
|----------|--------|

| | |
|----------|------|
| 96.0 kHz | ~2ms |
|----------|------|

DAW Roundtrip Software Monitoring Latency

@ 32 Sample Buffer (in to out)

| | |
|----------|-----|
| 44.1 kHz | 5ms |
|----------|-----|

| | |
|----------|-------|
| 96.0 kHz | 4.1ms |
|----------|-------|

Weight & Dimensions

| | | |
|----------|-------|------|
| Weights: | Unit: | 360g |
|----------|-------|------|

| | | |
|--|-----------|------|
| | Packaged: | 600g |
|--|-----------|------|

| | | |
|-------------|-------|---------------------------------|
| Dimensions: | Unit: | 140mm (w) x 67mm (h) x 67mm (d) |
|-------------|-------|---------------------------------|

| | | |
|--|-----------|-----------------------------------|
| | Packaged: | 172mm (w) x 88mm (h) x 97.5mm (d) |
|--|-----------|-----------------------------------|