

Product

Neutrik NC3MRX

Connection Type

Šifra: 18158

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Electrical

Cena: 8,50 EUR

Capacitance between contacts

Contact resistance

Dielectric strength

Insulation resistance

Rated current per contact

Rated voltage



Capacitance

> 2 GΩ (initial)

16 A

< 50 V

Mechanical

Cable O.D.

3.5 - 8.0 mm

Insertion force

≤ 20 N

Withdrawal force

≤ 20 N

Lifetime

> 1000 mating cycles

Wiresize

max. 2.5 mm²

Wiresize

max. 14 AWG

Wiring

Solder contacts

Locking device

Latch lock

Material

Boot

Polyurethan

Contact plating

2 μm Ag

Contacts

Bronze (CuSn8)

Insert

Polyamide (PA66)

Locking element

Zinc diecast (ZnAl4Cu1)

Shell

Zinc diecast (ZnAl4Cu1)

Shell plating

Nickel

Strain relief

Polyacetal (POM)

Environmental

Flammability

UL 94 V-0

Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C