

DAS AUDIO CL-6T - stropni ugradbeni zvučnik

Šifra: 2581

Kategorija proizvoda: 100V zvučnici ugradbeni

Proizvođač: DAS Audio

Cena: 52,00 EUR



Ceiling Loudspeakers

2-way passive full range ceiling loudspeaker incorporating a 6.5" cone low frequency transducer and a ferrofluid cooled soft dome high frequency unit with integral diffraction ring. The unit is equipped with a multi-tap line transformer. The system's low frequency driver is mounted on a plastic support with mounting tabs for fixing to ceiling surfaces. The front of the system shall be covered with a perforated metal grille.

Two-way full range ceiling speaker

Coaxial tweeter

High efficiency multi-tap transformer

6 in. low frequency driver

70V, 100V distributed systems

The 2-way passive full range ceiling loudspeaker shall incorporate an 6.5 inch cone low frequency transducer and a ferrofluid cooled 1 inch soft dome high frequency unit with integral diffraction ring. The low frequency voice coil shall be 1 inch in diameter. The high frequency voice coil shall be 0.5 inches in diameter.

The system specifications of a typical (transformer less) production unit shall be as follows: Average (RMS) power handling shall be 40W. Frequency range shall be of 60 Hz to 20 kHz. On-axis sensitivity (1W / 1m) shall be 90 dB SPL. Coverage angles shall be 100 degrees horizontal and vertical (average of 1/3rd octave bands from 500 to 8 kHz). Nominal impedance shall be 8 ohms.

The system's low frequency driver shall be mounted on a plastic support that houses mounting tabs for fixing to ceiling surfaces. Colour shall be white. The front of the system shall be covered with a perforated metal grille. The system shall incorporate a 15W multi-tap input transformer.

The system shall be a D.A.S. CL-6T.

| SPECIFICATIONS | |
|----------------------------|--------------------|
| Frequency Range (-10 dB) | 60 Hz - 20 kHz |
| Tap Selection 100V | 15-10-5-2.5-1.25 |
| Tap Selection 70V | 7.5-5-2.5-1.25-0.6 |
| On-Axis Sensitivity 1W/1 m | 90 dB SPL |
| Cut Out Diameter | 7.76 in. |
| Impedance | Line |
| Weight | 2.97 lbs |