Firma: Player doo
Adresa: Cvijete Zuzorić 7
Telefon: 097 714 8673
Fax:
PIB: 89978048220
E-mail: info@player.hr

DAS AUDIO CL-6T - stropni ugradbeni zvučnik



Šifra: 2581
Kategorija prozivoda: 100V zvučnici ugradbeni
Proizvođač: DAS Audio

Cena: 48,00 EUR

Ceiling Loudspeakers
2-way passive full range ceiling loudspeaker incorporating a 6.5" cone low frequency transducer and a ferrofluid cooled soft dome high frequency unit with integral diffraction ring. The unit is equipped with a multi-tap line transformer. The system’s low frequency driver is mounted on a plastic support with mounting tabs for fixing to ceiling surfaces. The front of the system shall be covered with a perforated metal grille.

- Two-way full range ceiling speaker
- Coaxial tweeter
- High efficiency multi-tap transformer
- 6 in. low frequency driver
- 70V, 100V distributed systems

The 2-way passive full range ceiling loudspeaker shall incorporate an 6.5 inch cone low frequency transducer and a ferrofluid cooled 1 inch soft dome high frequency unit with integral diffraction ring. The low frequency voice coil shall be 1 inch in diameter. The high frequency voice coil shall be 0.5 inches in diameter.

The system specifications of a typical (transformer less) production unit shall be as follows: Average (RMS) power handling shall be 40W. Frequency range shall be of 60 Hz to 20 kHz. On-axis sensitivity (1W / 1m) shall be 90 dB SPL. Coverage angles shall be 100 degrees horizontal and vertical (average of 1/3rd octave bands from 500 to 8 kHz). Nominal impedance shall be 8 ohms.

The system’s low frequency driver shall be mounted on a plastic support that houses mounting tabs for fixing to ceiling surfaces. Colour shall be white. The front of the system shall be covered with a perforated metal grille. The system shall incorporate a 15W multi-tap input transformer.

The system shall be a D.A.S. CL-6T.

SPECIFICATIONS	
Frequency Range (-10 dB)	60 Hz – 20 kHz
Tap Selection 100V	15-10-5-2.5-1.25
Tap Selection 70V	7.5-5-2.5-1.25-0.6
On-Axis Sensitivity 1W/1 m	90 dB SPL
Cut Out Diameter	7.76 in.
Impedance	Line
Weight	2.97 lbs

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.