

Neutrik // NL4MP - Speakon Chassis Connectors

NEUTRIK NL4MP - četveropolni ugradbeni speakon konektor

Šifra: 1263

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: 4,00 EUR



4 pole chassis connector, black D-size flange, countersunk thru holes, 3/16" flat tabs
The state-of-the-art chassis connector for loudspeaker / amplifier applications. They feature a unique locking system, robust plastic housing and high current silver plated contacts.

Features & Benefits

Standard current rating 30 Amp

Precise keyway for secure mating


Metal insert in locking area

Glass reinforced materials make it extremely robust and dependable

Accurate twist lock latching system

Airtight design - optimized for speaker applications

Image not found or type unknown



Product

Connector Type	Speakon
----------------	---------

Gender	male
--------	------

Electrical

Contact resistance	$\leq 3 \text{ m}\Omega$ (after lifetime)
--------------------	---

Dielectric strength	4 kVdc (peak)
---------------------	---------------

Insulation resistance	$> 1 \text{ G}\Omega$ (after dampheat)
-----------------------	--

Rated current per contact	30 A rms continuous
---------------------------	---------------------

Rated current per contact	40 A audiosignal, duty cycle 50 %
---------------------------	-----------------------------------

Rated voltage	250 V (Insulation)
---------------	--------------------

Attention	speakON is NOT to be used as an AC mains connector!
-----------	---

Mechanical

Lifetime	> 5000 mating cycles
----------	------------------------

Wiring	flat tabs for 3/16" (FASTON® 4.8 x 0.5 mm) or soldering
--------	---

Locking device	Quick Lock
----------------	------------

Mounting direction	front & rear
--------------------	--------------

Chassis shape	D
---------------	---

Layout	standard hole position, thru holes
--------	------------------------------------

Material

Contact plating	4 μm Ag
-----------------	--------------------

Contacts	Bronze (CuSn6)
----------	----------------

Shell	Polyamide (PA 6 30 % GR) black
-------	--------------------------------

Environmental

Approvals	UL,CSA
-----------	--------

Flammability	UL 94 HB
--------------	----------

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-30 °C to +80 °C
-------------------	------------------

