

## EIGHTEEN SOUND HD1040 - ugradbeni zvučnik

Šifra: 4882

Kategorija proizvoda: Ugradbeni zvučnici

Proizvođač: 18 Sound

**Cena: 65,00 EUR**



### Compression Driver 8 Ohm

- 1 inch exit throat
- 107 dB SPL 1W / 1m average sensitivity
- 44mm (1 3/4 inch) voice coil diameter
- 80 Watt program power handling
- Treated polyethylene diaphragm
- Proprietary phase plug design

The HD1040 one inch exit high frequency compression driver has been designed for use in high quality audio systems.

Equipped with proprietary Phase Plug architecture, the HD1040 has been designed to give high level manufacturing consistency and smooth coherent wave front at the horn entrance across the whole working frequency range. The phase plug with its short openings and high flare rate value assures low distortion and demonstrates remarkable improvements in mid-high frequency reproduction. The HD1040 diaphragm assembly is made by proprietary treated Polyethylene material. Thanks to its superior diaphragm dimensional stability (160°C), the polyethylene shows constant behaviour during its whole working life. Moreover, this particular material with its very high value of elasticity modulus, (50% more than standard Mylar and 100% more than polyimide film) is capable of superior transient and intermodulation distortion response. The flat suspension shape is designed to maintain low stiffness and low mid band distortion and response.

An edge-wound aluminum voice coil wound on proprietary treated Nomex completes the diaphragm assembly. Thanks to its physical properties, the proprietary treated Nomex former shows a 30% higher value of tensile elongation at a working operative temperature, (200°C) when compared to Kapton. This feature enables proper energy transfer control from the voice coil to the dome in real working conditions. Moreover, this proprietary former material is suitable for use in damp and wet environments.

The HD1040 powerful ceramic magnet assembly has been designed to obtain 16 KGauss in the gap within a compact ferrite motor structure.

## GENERAL SPECIFICATIONS

Throat Diameter	25,4 mm (1 in)
Rated Impedance	8 ohm
DC Resistance	5,3 Ohm
Minimum Impedance	7 Ohm at 4000Hz
AES power	40 W above 1,6 kHz
Program power	80 W above 1,6 kHz
Sensitivity(1W@1m)	107 dB
Frequency Range	1600Hz ÷ 20kHz
Recomm. Xover Frequency	1600Hz (12dB/oct slope)
Diaphragm Material	Treated polyethylene
Voice Coil Diameter	44,4mm (1 3/4 in)
Voice Coil Winding Material	Edge-wound aluminum
Magnet Material	Ferrite
Flux Density	1,6 T
BL Factor	7,4 N/A
Polarity	Positive voltage on + terminal gives positive pressure in the throat

## MOUNTING INFORMATION

Overall diameter	110 mm (4,3 in)
Mounting holes diameter	4 M6 holes 90° at Ø 76 mm (3 in)
Bolt circle diameter	76 mm (3 in)

Total depth	60,5 mm (2,38 in)
Net weight	1,8 Kg (4 lb)
Shipping weight	1,9 Kg (4,22 lb)
CardBoard Packaging dimensions	110x110x63 mm (4,3x4,3x2,5 in)